HERO

User Manual - \$12631, \$1110, \$1107, \$1108

Grab Rail 110kg





\$12631, \$1110, \$1107, \$1108

- S12631 Rails Grab Rail Bar S/S 32mm Hero Medical (Inseam Length 1070mm; Item Length 1170mm)
- S1110 Rails Grab Rail Bar S/S 32mm Hero Medical (Inseam Length 870mm; Item Length 970mm)
- S1108 Rails Grab Rail Bar S/S 32mm Hero Medical (Inseam Length 470mm; Item Length 570mm)
- S1107 Rails Grab Rail Bar S/S 32mm Hero Medical (Inseam Length 270mm; Item Length 370mm)



Instructions for Assembly

- 1. Determine the correct mounting position for both elbow ends, confirming you have selected a weight bearing location (ie wall stud or solid wall).
- 2. With the Grab Rail in position, mark the mounting drill points at each end (minimum of two).
- 3. Drill all mounting point holes.
- 4. Position the grab bar so that at least two of the screw holes align with the studs. Then mark each hole with a pencil.
- 5. Secure the Grab Rail with the fixings provided.

How to use the Grab Rail

A grab rail can be positioned to suit varying needs. Please consult with an Occupational Therapists or healthcare professional to ensure that it is suited to your needs.





SWL: 110kg

• This product is designed to be used daily in the home or community setting