



<11 km
Range per Charge



118 kg
Weight Capacity



100.3 cm
Turning Radius



GO GO®
ULTRA X

Ultra-Compact for Those on the GO!

Experience worry-free travel with the Go-Go® Ultra X, an ultra-compact scooter designed for effortless disassembly into five lightweight pieces with feather-touch technology. Conveniently access your belongings with the easy-to-reach front basket. This economical scooter ensures mobility and independence without compromising on quality or convenience.





Removable Battery Box




Feather Touch Disassembly



3 or 4 Wheel Option Available

| | |
|-------------------------------------|---|
| RANGE PER CHARGE (MAX) ¹ | Up to 11 km |
| MAXIMUM WEIGHT CAPACITY | 118 kg |
| TURNING RADIUS | 3W: 83.8 cm 4W: 100.3 cm |
| MAXIMUM SPEED ¹ | 6.4 km/h |
| LENGTH & WIDTH ³ | 3W: L: 94 cm W: 49.5 cm 4W: L: 100.3 cm W: 49.5 cm |
| SEAT TYPE WIDTH & DEPTH (STANDARD) | Compact, foldable seat W: 43 cm (17") D: 43 cm (17") |
| SEAT-TO-DECK HEIGHT | 40 cm - 43.8 cm |
| SEAT-TO-GROUND HEIGHT | 55 cm - 60 cm |
| GROUND CLEARANCE ⁵ | 6.3 cm at midframe 3.8 cm at motor |

| | |
|---|---|
| OVERALL WEIGHT (NOT INC BATTERY) ² | 3W: 34.5 kg 4W: 36.3 kg |
| WEIGHT OF HEAVIEST PIECE | 3W: 13.4 kg (front section) 4W: 15.4 kg (front section) |
| SUSPENSION | N/A |
| 3W/4W OPTION | 3W and 4W |
| FRONT TYRES | 3W: 8" solid 4W: 7" solid |
| REAR TYRES | 8" solid |
| BATTERY REQUIREMENTS ⁴ | (2) 12Ah |
| BATTERY CHARGER | Off-board, 2A |
| BATTERY WEIGHT | 4 kg each |
| COLOUR OPTIONS |  Red |

- Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
- Includes standard seat weight.
- Width of base (not including seat).
- Deep cycle (AGM or gel cell type recommended)
- Does not account for anti-tip clearance.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.