



<15.7 km
Range per Charge



204 kg
Weight Capacity



61.9 cm
Turning Radius



Jazzy®
ELITE HD

Enhanced Outdoor Performance

The Jazzy® Elite HD is a robust, heavy-duty wheelchair equipped with dual-motor, front-wheel drive technology. Its 14" drive wheels enhance outdoor performance, while the front-wheel drive design allows tight turning for superior indoor manoeuvrability in confined spaces. Large front wheels improve shock absorption for smooth climbing and, along with front anti-tip wheels, enable stable handling across diverse terrains.

Visit pridemobility.com.au for more information





Flip Up Foot Board





Dynamic Linx Joystick Controller



14" Solid Front Drive Wheels

RANGE PER CHARGE (MAX) ¹	Up to 15.7 km
MAXIMUM WEIGHT CAPACITY ⁴	204 kg
TURNING RADIUS	61.9 cm
MAXIMUM SPEED ¹	6.4 km/h
LENGTH & WIDTH ²	L: 90 cm W: 61 cm
WEIGHT OF HEAVIEST PIECE	44.9 kg
GROUND CLEARANCE	7.6 cm at foot-board mount
SEAT SIZE ⁴ WIDTH & DEPTH	W: 45.7 cm x D: 45.7 cm (18" x 18" - 20") W: 50.8 cm x D: 50.8 cm (20" x 20" - 22")
18" X 18" STANDARD SEAT WEIGHT	23.5 kg
HIGH-BACK SEAT-TO-FLOOR RANGE	50.8 cm - 55.8 cm

STANDARD ELECTRONICS	60A, Dynamic linx
DRIVE TRAIN	Two motor, front-wheel drive
BRAKING SYSTEM	Regenerative and electro-mechanical
SUSPENSION TYPE	Limited
FRONT CASTORS	3" solid anti-tip
DRIVE WHEELS	14" solid
REAR CASTORS	6" solid
BATTERY REQUIREMENTS ³	(2) 55Ah, 12V
BATTERY CHARGER	5A, off-board
BATTERY WEIGHT	16.8 kg each
COLOUR OPTIONS	 Red  Blue

1. Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
2. Width of base (not including seat).
3. Deep cycle (AGM or gel cell type recommended)
4. Maximum weight capacity is reduced to 181 kg on 18" wide seat configuration.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.