



<24 km
Range per Charge



136 kg
Weight Capacity



55.5 cm
Turning Radius



Jazzy®
SELECT 6

Enjoy Freedom and Control

Sporty, sophisticated, and uniquely designed, the Jazzy® Select 6 delivers powerful performance and unmatched stability. Featuring Pride's patented Active-Trac® Suspension, this compact powerhouse combines a tight turning radius with six-wheel stability and an articulating beam, providing a smooth, stable ride indoors and over even outdoor terrain. With a depth-adjustable seat for personalized comfort, the Jazzy® Select 6 keeps things simple, so you can enjoy every journey.





Active-Trac® Suspension




6" Castors Front & Rear For Stability



Height And Depth-Adjustable Foot Platform

RANGE PER CHARGE (MAX) ¹	Up to 24 km
MAXIMUM WEIGHT CAPACITY	136 kg
TURNING RADIUS	55.5 cm
MAXIMUM SPEED ¹	6.4 km/h
LENGTH & WIDTH ²	L: 90 cm W: 59.6 cm
WEIGHT OF HEAVIEST PIECE	44.1 kg
GROUND CLEARANCE	4.4 cm at motor mount
SEAT SIZE	W: 45.7 cm x D: 45.7 cm (18" x 18" - 20")
STANDARD 18" X 18" SEAT WEIGHT	19.9 kg
HIGH-BACK SEAT-TO-FLOOR RANGE	53.9 cm - 59 cm

STANDARD ELECTRONICS	40A, PG GC3
DRIVE TRAIN	Two motor, in-line, mid-wheel drive
BRAKING SYSTEM	Regenerative and electro-mechanical
SUSPENSION TYPE	Active-Trac® (ATX)
FRONT CASTORS	6" solid
DRIVE WHEELS	10" solid
REAR CASTORS	6" solid
BATTERY REQUIREMENTS ⁴	(2) 35Ah, 12V
BATTERY CHARGER	Off-board, 3.5A
BATTERY WEIGHT	10.5 kg each
COLOUR OPTIONS	 Red

1. Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
2. Width of base (not including seat).
3. Deep cycle (AGM or gel cell type recommended)

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.